

# ActEV19 SDL Evaluation CLI Programming Primer

**April 16, 2021**

Here are the necessary steps to go through in order to build a deliverable form of your ActEV system using the Abstract ActEV Evaluation CLI and test it.

There are several steps to completing this process:

1. Git fork and Git clone the ActEV Eval CLI,
2. Adapt/modify the function implementations for your system,
3. Test your implementation,
4. Update your CLI with the latest abstract CLI code,
5. Complete Final Delivery Checks on a new Ubuntu installation,
6. Deliver your ActEV CLI implementation.

## **Step 1: Git fork and Git clone the ActEV Eval CLI**

Go to the diva evaluation CLI repository by clicking on the following URL:

[https://gitlab.kitware.com/actev/diva\\_evaluation\\_cli](https://gitlab.kitware.com/actev/diva_evaluation_cli)

Click on the “Fork” button to make a copy of the repository in your own space.

Git clone your repository to make changes. 2 relevant branches are available:

- *master*: contains the abstract CLI to implement, you should start from this branch.
- *baseline\_system\_master*: an implementation example to help you.

*Advice:*

- *You should execute a ‘git pull’ command occasionally to get the latest updates from the forked repository.*
- *You should use the master branch to start your implementation*

## **Step 2: Adapt/modify the function implementations for your system**

The CLI contains three directories namely:

- *bin/*: a NIST-maintained directory composed of commands parser and some commands implemented by NIST. Users should not modify the contents of this directory
- *src/*: a User-maintained directory that will include your CLI implementation.
- *container\_output/*: set of directories containing your own system output on the validation data sets.
- *doc/*: graphs and documentation of the entry points.

*src* includes a directory named “entry points” that contains functions that have to be completed. Each command is associated with a specific entry point and calls this one during the command execution. Generally, entry point functions are only used to call a script that really handles the request. These scripts can be put inside the *src* directory as well. See the baseline system master branch to have more information. Moreover, *bin* directory should not be modified as it is maintained by NIST.

*container\_output* is a directory containing at least one generated output for at least the most recent validation dataset. By default, it contains the output and the chunk file generated by the baseline system as well as the file index and the activity index of the validation set used. The naming convention is:

*<Dataset>\_<File>.json*

Where:

- *<Dataset>* ::= one of published data sets. E.g., ActEV-Eval-CLI-Validation-Set3
- *<File>* ::= "file", "activity", "chunk", "output"

### Step 3: Test your implementation

Once you want to test your work, you can simply install the CLI by using the following commands:

```
$ cd diva_evaluation_cli
$ diva_evaluation_cli/bin/install.sh
$ actev -h
```

The last command should give the help of the CLI if it is well installed.

As the CLI is installed as an editable package, you do not need to reinstall it after a modification.

Execute:

- a specific command to debug it(e.g. *actev system-setup*)
- *actev system-setup* followed by *actev exec* with the right arguments to run every step in order to get an output result.
- *actev validate-execution* to compare your result with the data set results included in *container\_output*.

Advice:

Execute *actev validate-system* often to make sure that your implementation is still valid with what NIST expects. This involves:

- Entry point method signatures must not be modified. You cannot add, modify or remove a parameter in the signature.
- Structure of the project must not be modified. You cannot modify */bin*. You may write your implementation under */src* and some additional outputs in */container\_output*.
- Some expected outputs are provided in the */container\_output/<Dataset>* directory. The files within each data set directory are the following: *<Dataset>\_file.json*, *<Dataset>\_activity.json*, *<Dataset>\_chunk.json* and *<Dataset>\_output.json*.

- The output that you put in *container\_output* should be consistent with the system output for Activity Detection (AD).
- For example, the file listing for ActEV-Eval-CLI-Validation-Set3 is:

```
/container_output/
/container_output/ActEV-Eval-CLI-Validation-Set3
/container_output/ActEV-Eval-CLI-Validation-Set3/ActEV-Eval-CLI-Validation-Set3_activity.json
/container_output/ActEV-Eval-CLI-Validation-Set3/ActEV-Eval-CLI-Validation-Set3_chunk.json
/container_output/ActEV-Eval-CLI-Validation-Set3/ActEV-Eval-CLI-Validation-Set3_file.json
/container_output/ActEV-Eval-CLI-Validation-Set3/ActEV-Eval-CLI-Validation-Set3_output.json
```



```
container_output/ActEV-Eval-CLI-Validation-Set3_<TeamName>/ActEV-Eval-CLI-Validation-Set3_output.json
\  
-a \  
container_output/ActEV-Eval-CLI-Validation-Set3_<TeamName>/ActEV-Eval-CLI-Validation-Set3_activity.json
\  
-f \  
container_output/ActEV-Eval-CLI-Validation-Set3_<TeamName>/ActEV-Eval-CLI-Validation-Set3_file.json \  
-R \  
~/results
```

3. Pass checks on the system delivery by executing 'actev validate-system'
4. Make sure that your system can run after a reboot of your machine (by including environment variable in your .bashrc)

### Step 6: Deliver your ActEV CLI implementation

Once you have passed Step 5, you can deliver your system via URL:

Sign in to access the web platform (<https://actev.nist.gov/>), click on "ActEV SDL Evaluation" and create a new system. Once it is done, submit a URL pointing to your CLI implementation as well as the credentials (username, password and/or token) to access it so that NIST can download it, install it on a new Openstack instance and test it.

*Currently, NIST supports git repository or web accessible compressed tar/zip file. Moreover, this option implies that your 'actev system-setup' command implementation is able to install all your package dependencies on a fresh Ubuntu system without any manual assistance.*

### What happens when I trigger the validation pipeline?

A new Ubuntu VM is created and your CLI implementation is downloaded and executed alongside with the last CLI implementation from NIST. More details about the execution of the commands can be found in the repository of the CLI. If your system processes the validation dataset successfully, the VM is saved as a *snapshot* and kept for further analysis in a sequestered environment.

#### Change Log:

- June 19, 2019 - Revised for SDL
- July 25, 2019 - Identified Validation Set 3 as the validation data set
- April 16, 2021 - Reviewed